

**Patch Cord Cat. 6, U/UTP, 4P, LSZH, gray, RJ45/u-
RJ45/u, 2.0 m**



DESCRIPTION

Cable identification: U/UTP
 Outer jacket: LSZH
 Conductor diameter copper strand: AWG 26/7
 Screened in pairs: no
 Overall screen: no
 Outer diameter: max. 6.0 mm

030.6001 / similar product

TECHNICAL DATA

DESCRIPTION	VALUE/VALUE RANGE
Standard / norm	Compliant with Cat. 6 Class E (250 MHz) requirements: ISO/IEC 11801 Compliant with Cat. 6 component standard IEC 60603-7-4 Compliant with Cat. 6 component standard IEC 60603-7-5 Fulfilled the standard IEC 61935-2
Protection class IP	IP 20
PoE	Yes
Connector class	connector
Shielding connector (A)	unshielded
Connector type (A)	RJ45
Category connector (A)	Cat. 6
Shielding connector (B)	unshielded
Connector type (B)	RJ45
Category connector (B)	Cat. 6
Wiring diagram	TIA-568A
Cable type	Patch cord
Cable category	Cat. 6
Shielding	U/UTP
Jacket material	LSZH
Cable jacket characteristics	Cable, metal-free zero-halogen
Cable overall diameter	6.0 mm
Conductor	AWG 26/7
Number of wires	8